

FOR MORE INFORMATION  
VISIT TEXSTYLE'S WEBSITE  
[WWW.TEXSTYLE.COM.AU](http://WWW.TEXSTYLE.COM.AU)  
OR PHONE 03 9729 9970

## TECHNICAL DATA

<b>Composition</b>	30% Polyester   70% PVC
<b>Width</b>	3,000mm
<b>Weight</b>	413gsm
<b>Thickness</b>	0.72mm
<b>Light fastness</b>	>7 (Blue wool scale), fully fade resistant
<b>Openness</b>	6%
<b>Tensile Strength</b>	Warp 157.5 daN / 5cm   Weft 139.9 daN / 5cm
<b>Tearing Strength</b>	Warp 20 daN   Weft 16.5 daN
<b>Protection</b>	Mould and mildew protection
<b>Flame Retardant</b>	Tested to AS1530.3
<b>Cleaning</b>	Wipe clean with warm soapy water, and damp cloth

## LIGHT & SOLAR PROPERTIES

Fabric Name	Colour	USA Standard Tested To Ashrae 74-73								
								Shading Coefficients (Sc)		
		Ts	Rs	As	Tuv	Tv	O-f	3mm CL.	6mm CL.	6mm H.A.
Dakota	Quartz	26	63	11	8	25	6	0.38	0.38	0.34
	Marble	25	50	25	5	23	6	0.37	0.36	0.34
	Ore	23	47	30	6	22	6	0.38	0.37	0.40
	Granite	7	4	89	7	11	6	0.74	0.70	0.51
	Flint	10	11	79	8	13	6	0.70	0.67	0.49
	Coal	8	4	88	8	12	6	0.74	0.70	0.51



ROLLER

PANEL

ROMAN