

# SOLAR VIEW

Designed for control of heat and light  
Excellent flame retardancy  
Oeko-Tex and Ecospecifier certified



TEXTSTYLE

FOR MORE INFORMATION  
VISIT TEXTSTYLE'S WEBSITE  
[WWW.TEXTSTYLE.COM.AU](http://WWW.TEXTSTYLE.COM.AU)  
OR PHONE 03 9729 9970

## TECHNICAL DATA

<b>Composition</b>	30% Polyester   70% PVC
<b>Width</b>	2,500mm & 3,000mm
<b>Weight</b>	530gsm
<b>Thickness</b>	0.75mm
<b>Fabric Count</b>	Warp 72 threads / 5cm   Weft 66 threads / 5cm (ISO 5084)
<b>Light fastness</b>	8 (Blue wool scale), fully fade resistant
<b>Openness</b>	5 - 6% depending on the colour
<b>Tensile Strength</b>	Warp 267 daN / 5cm   Weft 257 daN/5cm (ISO 1421)
<b>Tearing Strength</b>	Warp 29 daN   Weft 27 daN (ISO 4674)
<b>Protection</b>	Mould and mildew protection
<b>Flame Retardant</b>	Tested to AS1530.3   NFPA 701
<b>Cleaning</b>	Wipe clean with warm soapy water, and damp cloth

## LIGHT & SOLAR PROPERTIES

Fabric Name	Colour	USA Standard Tested To Ashrae 74-73								
		Ts	Rs	As	Tuv	Tv	O-f	Shading Coefficients (Sc)		
								3mm CL.	6mm CL.	6mm H.A
Solar View	White	22	64	14	7	21	7	0.36	0.36	0.33
	Alabaster	20	61	19	6	19	6	0.38	0.38	0.34
	Off White	21	63	16	6	21	7	0.37	0.37	0.34
	Cotton	18	61	21	6	18	6	0.37	0.37	0.34
	Bone / Off White	17	57	26	6	17	6	0.40	0.40	0.35
	Taupe	12	41	47	7	13	7	0.50	0.50	0.40
	Grey	12	30	58	7	14	7	0.58	0.58	0.43
	Charcoal	6	5	89	6	10	6	0.73	0.73	0.51
	Bronze / Charcoal	6	7	87	6	9	6	0.72	0.72	0.50
	Black / Copper	7	8	85	7	11	7	0.71	0.71	0.50
	Black	7	4	89	6	10	6	0.74	0.74	0.51
	Platinum	7	10	83	11	7	7	0.72	0.68	0.50

